Graphical Abstract

Free Sulfurous Acid (FSA) Inhibition of Biological Thiosulfate Reduction (BTR) in the Sulfur Cycle-driven Wastewater Treatment Process

Jin Qian^{a,b,c,*}, Lianlian Wang^a, Yaoguo Wu^a, Philip L Bond^g, Yuhan Zhang^a, Xing Chang^a,
Baixue Deng^a, Li Wei^d, Qin Li^{e,f}, Qilin Wang^{e,g*}

^aDepartment of Applied Chemistry, School of Natural and Applied Sciences, Northwestern Polytechnical University, NO. 127 West Youyi Road, Xi'an 710072, China

^bState Key Laboratory of Geohazard Prevention and Geoenvironment Protection, Chengdu University of Technology, China

^cResearch Center for Ecology and Environmental Sciences, Northwestern Polytechnical University, NO. 127 West Youyi Road, Xi'an 710072, China

^dState Key Laboratory of Urban Water Resource and Environment, Harbin Institute of Technology, Harbin 150090, China

^eGriffith School of Engineering, Griffith University, Nathan Campus, QLD 4111, Australia

^fQueensland Micro- and Nanotechnology Centre, Griffith University, Nathan, QLD 4111, Australia

^gAdvanced Water Management Centre (AWMC), The University of Queensland, QLD 4072, Brisbane, Australia

*Corresponding authors:

E-mail: qilin.wang@griffith.edu.au (Q. Wang); Tel.: +61 7 33463229; Fax: +61 7 33654726

23 E-mail: qianjin131@yahoo.com.hk (J. Qian)

24

25 **Abstract:** A sulfur cycle-based bioprocess for co-treatment of wet flue gas desulfurization
26 (WFGD) wastes with freshwater sewage has been developed. In this process the removal of
27 organic carbon is mainly associated with biological sulfate or sulfite reduction. Thiosulfate is a
28 major intermediate during biological sulfate/sulfite reduction, and its reduction to sulfide is the
29 rate-limiting step. In this study, the impacts of saline sulfite (the ionized form: $\text{HSO}_3^- + \text{SO}_3^{2-}$)
30 and free sulfurous acid (FSA, the unionized form: H_2SO_3) sourced from WFGD wastes on the
31 biological thiosulfate reduction (BTR) activities were thoroughly investigated. The BTR activity
32 and sulfate/sulfite-reducing bacteria (SRB) populations in the thiosulfate-reducing up-flow
33 anaerobic sludge bed (UASB) reactor decreased when the FSA was added to the UASB influent.
34 Batch experiment results confirmed that FSA, instead of saline sulfite, was the true inhibitor of
35 BTR. And BTR activities dropped by 50% as the FSA concentrations were increased from
36 8.0×10^{-8} to 2.0×10^{-4} mg H_2SO_3 -S/L. From an engineering perspective, the findings of this study
37 provide some hints on how to ensure effective thiosulfate accumulation in biological
38 sulfate/sulfite reduction for the subsequent denitrification/denitritation. Such manipulation
39 would result in higher nitrogen removal rates in this co-treatment process of WFGD wastes with
40 municipal sewage.

41

42 **Key words:** biological thiosulfate reduction (BTR); sulfate/sulfite-reducing bacteria (SRB);
43 saline sulfite ($\text{HSO}_3^- + \text{SO}_3^{2-}$); free sulfurous acid (FSA, H_2SO_3)

44

1. Introduction

Sulfur bioconversion-associated sewage treatment processes have been reported extensively in the last two decades, among which biological sulfate reductions (BSR) and biological reduced sulfur (i.e. sulfide, thiosulfate, elemental sulfur, etc) oxidations (BSO) play an essential role in the removal of organics and nitrogen respectively (Lens et al., 1998; Cardoso et al., 2006; Manconi et al., 2007; Mora et al., 2014). By linking BSR with BSO and based on the sulfur sources from wet flue gas desulfurization (WFGD) wastes, an integrated process for co-treatment of fresh sewage and WFGD wastes has been developed (Qian et al., 2013). This co-treatment process mainly depends on the sulfur bioconversions from sulfate/sulfite (alkaline absorption of WFGD wastes) reduction to sulfide/thiosulfate, followed by sulfide/thiosulfate oxidation to sulfate (see Fig. S1 in Supporting Information for schematic diagram of the co-treatment process). Due to the low biomass yields of the bacteria involved in this process, i.e. sulfate/sulfite-reducing bacteria (SRB), sulfur oxidizing-denitrifying bacteria and autotrophic nitrifying bacteria, the sludge production rate is only 0.03 to 0.09 g MLVSS/g COD (Jiang et al., 2013; Qian et al., 2015a) (MLVSS: mixed liquor volatile suspended solids; COD: chemical oxygen demand), and this results in energy savings and reduction in greenhouse gas emission during the sludge treatment.

In this co-treatment process, sulfite produced from the WFGD wastes is one of the major sulfur compounds for biological energy conversions. However, negative effects of sulfite in both ionized form (saline sulfite: $\text{SO}_3^{2-} + \text{HSO}_3^-$) and unionized forms (free sulfurous acid, FSA: H_2SO_3) on microorganisms including SRB have been reported. Previous studies have found that

saline sulfite inhibition on sulfate/sulfite reduction occurs at concentrations as low as 16 mg S/L (Weijma et al., 2000). Zan et al. (2016) recently demonstrated that FSA from 0.002 to 1 mg H_2SO_3 -S/L instead of saline sulfite directly causes the lysis of microorganisms. This implies that FSA, rather than saline sulfite, is the factor exerting the antimicrobial effect on SRB.

During biological sulfate/sulfite reduction, thiosulfate (i.e. $\text{S}_2\text{O}_3^{2-}$) is an important intermediate and its reduction to sulfide is the rate-limiting step during the biological $\text{SO}_4^{2-}/\text{SO}_3^{2-}$ reaction (Brunner and Bernasconi, 2005) (see Fig. S2). Additionally, thiosulfate is important in sulfur dependent denitrification as its oxidation is reported to drive denitrification 4-8 times faster than oxidation by sulfide (Cardoso et al., 2006). Therefore, it is important to understand the potential effects of saline sulfite and FSA on these important thiosulfate transformations, including that of biological thiosulfate reduction (BTR). This insight will determine the role of saline sulfite and FSA in this sulfur cycle-based treatment of WFGD wastes as well as to shed light on how to maintain effective $\text{S}_2\text{O}_3^{2-}$ accumulation for high nitrogen removal in the subsequent $\text{S}_2\text{O}_3^{2-}$ -driven denitrification/denitritation. To the best of the authors' knowledge, although the effects of saline sulfite and FSA effects on microbial inactivation (Chang et al., 1997), biological $\text{SO}_4^{2-}/\text{SO}_3^{2-}$ reduction (Weijma et al., 2000) and sludge treatment (Zan et al., 2016) have been examined, no detailed investigations of the effects of saline sulfite and FSA on BTR have been carried out so far.

This study aims to thoroughly explore the effects of saline sulfite and FSA on BTR. Long-term impacts of saline sulfite and FSA on BTR activities as well as microbial community structures

were investigated during the co-treatment process of WFGD wastes with sewage in an up-flow anaerobic sludge bed (UASB) reactor. Batch experiments were conducted and the quantitative relationship between the BTR activities and FSA concentrations were determined. The findings of this study also identified strategies on how to achieve $\text{S}_2\text{O}_3^{2-}$ accumulation during biological $\text{SO}_4^{2-}/\text{SO}_3^{2-}$ reduction, which is then utilized for high nitrogen removal in the co-treatment process.

2. Materials and Methods

2.1 UASB reactor setup and operation

A UASB reactor with an effective reactor volume of 1.0 L (height: 51 cm, diameter: 5 cm) was established (Fig. S3). The seeding sludge for the UASB reactor was from a lab-scale biological sulfate reduction–sequential batch reactor (SBR) (see Table S1 for detailed operating conditions). At which time the SBR was at steady state achieving at least 90% sulfate and organic carbon removal. 500 mL of mixed liquor sludge was taken from this SBR reactor and added to the UASB reactor, resulting in an initial MLVSS concentration of 4300 mg/L. Although the typical COD values of municipal sewage in Mainland China and Hong Kong are between 300 and 400 mg/L (equivalent to about 150 to 200 mg SO_4^{2-} -S/L), 200 mg COD/L was employed for the UASB reactor's influent as the electron accepting capacity of $\text{S}_2\text{O}_3^{2-}$ is only half of that of SO_4^{2-} . The temperature of UASB reactor was kept at $25\pm 1^\circ\text{C}$ in an air conditioned room and its hydraulic retention time (HRT) was maintained at 4 h during the operation. The internal recirculation flow rate was maintained at three times the influent flow rate, this ensured effective mass transfer between the bulk liquid and the biomass.

111

112 The reactor was continuously operated for 181 days consisting of 5 stages during which the
113 same influent organic carbon (200 mg COD/L, sodium acetate was used as the sole organic
114 source) and thiosulfate (220 mg S/L) concentrations were maintained, but varying pH (7.0-8.5),
115 influent saline sulfite (0-150 mg S/L) and influent FSA concentrations ($0-6.0 \times 10^{-4}$ mg S/L) were
116 applied. The detailed experimental conditions for each stage are shown in Table S2. Overall,
117 Stage I (Day 1 to Day 21) was to evaluate the BTR performance of the UASB reactor at pH 7.0
118 in the absence of added saline sulfite and FSA. Stages II- IV were to examine the effect of saline
119 sulfite and FSA on the BTR in the UASB reactor. The different FSA concentrations in Stages
120 II-IV were obtained by varying the pH and Na_2SO_3 concentrations (see Table S2). The operating
121 conditions of the UASB reactor at Stage V were the same as those at Stage I. This was to
122 determine whether the inhibited BTR, caused by the saline sulfite and FSA, could be recovered
123 after removal of the influent saline sulfite and FSA.

124

125 During the UASB reactor's operation, samples of both the influent and effluent were regularly
126 drawn for analyses of COD, sulfide, saline sulfite and thiosulfate. Sludge samples were taken
127 periodically from the bottom, middle, and top of the reactor to determine the mixed liquor
128 suspended solids (MLSS)/MLVSS concentration. In addition, microbial community structures
129 of the sludge were analyzed at the end of Stages I (Day 21), III (Day 97) and V (Day 181)
130 during the UASB reactor operation.

131

132 *2.2 Batch Tests*

Three sets of batch tests were performed to evaluate the effect of saline sulfite and FSA and reveal the true inhibitor on BTR. These were performed on sludge taken from the abovementioned UASB reactor at the end of its operation (Stage V). For each batch test, the sludge was washed, using a synthetic wastewater (Table S3), three times to remove the background substrate (i.e. acetate, thiosulfate and sulfide, etc). 2 L serum flasks were used as the batch reactors for all the tests. Nitrogen gas was purged into each batch reactor before the assay for half an hour to exclude oxygen and maintain anaerobic conditions. Afterwards, all reactor flasks were sealed tightly with butyl rubber stoppers and aluminum crimp seals. The reactors were well mixed with magnetic stirrers at 150 rpm. The temperature of each reactor was kept at 25 ± 1 °C in an air-conditioned room. Sodium acetate was used as the sole organic carbon source. In order to exclude the possible influence of generated S^{2-}/H_2S on BTR activity (O’Flaherty et al., 1998), an $FeCl_2$ solution, at 200 mg Fe^{2+}/L was added to each reactor for all the tests (O’Flaherty et al., 1998). During the batch experiments, the mixed liquor was sampled regularly for the analysis of thiosulfate, saline sulfite and FSA.

2.2.1 Batch Test I: BTR under different pH conditions in the absence of saline sulfite and FSA

Batch test I was conducted to evaluate the effect of pH on BTR in the absence of added saline sulfite and FSA. The pH in four reactors (i.e. Batch reactors 1–4) was adjusted to 6.0, 7.0, 8.0 and 9.0, respectively, by addition of Na_2HPO_4/NaH_2PO_4 buffer solution, as shown in Table S4. Initial acetate and $S_2O_3^{2-}$ concentrations were 200 mg COD/L and 200 mg S/L, respectively, by addition of sodium acetate and $Na_2S_2O_3$ stock solutions. The batch tests lasted for 24 h.

2.2.2 Batch Test II: Examine the overall effects of saline sulfite and FSA on BTR activities

Batch Test II was carried out to investigate the overall effects of both saline sulfite and FSA on the BTR activities. The same amount of thiosulfate (200 mg S/L) was added into the four batch reactors (i.e. Batch Reactors 5–8, see Table S4). The saline sulfite and FSA concentrations were 50~200 mg S/L, and $2.0 \times 10^{-4} \sim 8.0 \times 10^{-4}$ mg H_2SO_3 -S/L, respectively (see Table S4). The pH in each reactor was controlled at 7.0 ± 0.1 using the $\text{Na}_2\text{HPO}_4/\text{NaH}_2\text{PO}_4$ buffer solution. The batch tests lasted for 24 hours.

2.2.3 Batch Test III: BTR under different FSA levels

To explore the correlation between FSA concentration and BTR activities, Batch Test III was also conducted by changing the pH and initial Na_2SO_3 concentrations, according to Eqs. (1) and (2). Different amounts of Na_2SO_3 (i.e. 50~200 mg S/L) and different pH levels (i.e. 6.0~9.0) were applied to the six batch reactors (i.e. Batch Reactor 9–14) in this test, resulting in the different initial FSA concentrations (i.e. $8.0 \times 10^{-8} \sim 0.015$ mg S/L) in each batch reactor. Detailed information of each batch reactor test is shown in Table S4. The batch tests lasted for 24 h.

2.3 Sampling and Chemical/Physical Analysis

Mixed liquor samples from the batch reactors were taken periodically using a 10-mL syringe and these were immediately filtered through disposable Millipore filters (0.22 μm pore size).

Saline sulfite concentrations were determined by titration after sample pretreatment as detailed in Qian et al. (2015a). Thiosulfate and acetate were detected with an ion chromatograph (DIONEX-900). Sulfide was measured by the methylene blue method after sample pretreatment with NaOH and ZnAc (APHA, 2005). MLSS/MLVSS were measured according to the Standard Method (APHA, 2005). pH and temperature were monitored using a multi-meter electrode during each test (PHSJ-4F).

As thiosulfate is an intermediary compound in biological sulfite reduction, BTR activity cannot be directly derived from the profile of $S_2O_3^{2-}$ concentration versus time. In this study, the BTR activity was represented by the rate of thiosulfate utilization (derived from the profile of $S_2O_3^{2-}$ concentration versus time) plus the biological sulfite reduction rate (derived from the profile of saline sulfite concentration versus time) and expressed as $kg\ S_2O_3^{2-}\text{-S/d/m}^3$ in the UASB reactor and $mg\ S_2O_3^{2-}\text{-S/g MLVSS/h}$ in the batch reactor, respectively.

2.4 Microbial analysis

Sludge samples from the UASB reactor were collected at the end period of Stages I (Day 21), III (Day 97) and V (Day 181) to analyze the structure of microbial communities. The samples were collected by centrifugation under 12,000 rpm for 10 minutes. Around 0.5 g of sludge pellet was stored for each sample at $-80\ ^\circ\text{C}$ until the DNA extractions were performed. Genomic DNA was extracted using the PowerSoil DNA Isolation Kit (MoBio Laboratories, Inc., Carlsbad, CA) following the manufacturer's protocols. The quality and quantity of DNA were checked with a NanoDrop device (ND-1000, thermo Fisher, USA).

199

200 The primer pair 515 F and 926 R targeting the hypervariable V1 and V3 regions was used to
201 amplify the bacterial 16S rRNA gene (Quince et al., 2011). Barcode sequences were
202 incorporated between the 454 adaptor and the forward primer (Table S5). Each 100 µL PCR
203 reaction mixture contained 5 U of Pfu Turbo DNA polymerase (Stratagene, La Jolla, CA, USA),
204 1× Pfu reaction buffer, 0.2 µM of dNTPs (TaKaRa, Dalian, China), 0.1 µM of each primer and
205 20 ng of genomic DNA template. PCR was performed on a thermal cycler (Bio-Rad, USA) with
206 the cycles including an initial denaturation at 94°C for 5min, followed by 30 cycles of 94°C for
207 30s, 53°C for 30s and 72°C for 45s; and a final extension at 72 °C for 10 min. PCR products
208 were purified using Agarose Gel DNA Purification Kit (TaKaRa, China) and quantified with the
209 NanoDrop device. The purified PCR amplicons were sequenced using the ROCHE 454 FLX
210 Titanium platform (Roche, Basel, Switzerland) at the National Human Genome Centre of China
211 (Shang Hai, China). Analysis of the sequences obtained followed the procedures reported in
212 Qian et al. (2015b).

213

214 **3. Results and Discussion**

215 *3.1 UASB reactor performance under different operating conditions*

216 In Stage I, as the sulfur source was transformed from sulfate (for the sludge cultivation) to
217 thiosulfate in the UASB reactor, thiosulfate reduction efficiency (65%) and organic carbon
218 removal efficiency (60%) were low initially (Fig. 1a and b). However, the sulfide generation
219 became stable at the end of Stage I and reached 185 mg S/L in the UASB effluent (Fig. 1a),
220 indicating approximately 84% ($185/220 \times 100\%$) thiosulfate was converted to sulfide and the

BTR rate was 1.11 kg $\text{S}_2\text{O}_3^{2-}$ -S/d/m³. Correspondingly, the effluent COD concentrations stabilized at around 18 mg /L after 16 days, corresponding to a COD removal efficiency of 90% through BTR (Fig. 1b).

(Position for Fig. 1)

During the UASB reactor operation Stage II the influent contained 50 mg S/L of Na_2SO_3 (pH 7.0, equivalent to 2.0×10^{-4} mg FSA-S/L). It was seen that the effluent sulfide concentration decreased from 185 mg S/L in Stage I to 120 mg S/L in Stage II (Fig. 1a) and the BTR rate decreased from 1.11 to 0.93 kg $\text{S}_2\text{O}_3^{2-}$ -S/d/m³. At the same time, the COD removal efficiency dropped immediately and stabilized at about 75%. This implied an inhibitory effect of saline sulfite and FSA on the BTR. As the influent Na_2SO_3 concentration was increased to 150 mg S/L (FSA at 6.0×10^{-4} mg S/L), sulfide generation in UASB reactor's effluent dropped from 185 mg S/L (in Stage I without FSA) to 99 mg S/L in Stage III. In Stage III the BTR rate had also dropped to 0.8 kg $\text{S}_2\text{O}_3^{2-}$ -S/d/m³, which was only 72% of that in Stage I. As well, the COD removal efficiency continued to drop to 65% (Fig. 1b). In Stage IV, the UASB reactor's influent pH was raised to 8.5 and the influent Na_2SO_3 concentration was kept at 150 mg S/L, corresponding to a lowered FSA concentration of 1.2×10^{-6} mg FSA-S/L. In this stage, sulfide generation, thiosulfate reduction as well as organic carbon removal were restored to some extent. As shown in Fig. 1a and b, there were increases in the BTR rate to 0.96 kg $\text{S}_2\text{O}_3^{2-}$ -S/d/m³, the effluent sulfide concentration to 157 mg S/L and the organic carbon removal efficiency to about 80%. Therefore, in addition to the Na_2SO_3 concentration, pH may also play a role in the BTR

activity, suggesting that the combined effects of pH and Na₂SO₃ (i.e. FSA) might be the true inhibitor on the BTR activity in the UASB reactor.

At Stage V, the operating conditions of the UASB reactor were fully restored to those of Stage I. After 20 days into Stage V it was seen that the BTR rate (1.06 S₂O₃²⁻-S/d/m³), sulfide generation (174 mg S/L) and the COD removal efficiency (89%) in UASB reactor were comparable with those in Stage I (Fig. 1). Thus, indicating the biomass activity in the UASB reactor had recovered after eliminating the saline sulfite/FSA addition to the influent.

3.2 Microbial community shift in UASB reactor

9812, 8174 and 9578 quality sequence reads of the 16S rRNA gene (with an average read length of 374 bp) were obtained from the UASB reactor at the end of Stages I, III and V respectively (Fig. 2a). The sequences were clustered into 564, 959 and 670 operational taxonomic units for the three tested sludge samples in Stage I, III and V respectively (Table S6).

(Position for Fig. 2)

Excluding the unclassified Bacteria, altogether, 9 bacterial phyla were recovered from the three sludge samples. The majority of the sequences belong to the Firmicutes, Proteobacteria and Bacteroidetes phyla (Fig. 2b). However, at the phylum level microbial community changes are not obvious between the stages with and without the FSA addition to the reactor's influent. Therefore, the microbial communities were analyzed at the class and genus levels (Fig. 2c and

d). The sequences were further classified into 17 classes (Fig. 2c), and in all three stages, the dominant classes were Bacilli, Deltaproteobacteria and Clostridia. However, variation of abundances of the classes was detected between the different Stages, with the Deltaproteobacteria having the most significant shifts. As most of the functional SRB genera belong to the class Deltaproteobacteria (Castro et al., 2000), it is possible that this relates to variation of the SRB populations corresponding to the absence and presence of FSA.

Within the microbial community analysis at the genus level, four to five types of recognized SRB were detected at different levels in each stage, with *Desulfomicrobium* and *Desulfobulbus* as the most two abundant genera (see Fig. 2d and Table S7). Species of these two genera can reduce $S_2O_3^{2-}$ to HS^-/S^{2-} coupled with the oxidation of organic substrates that include lactate, pyruvate, glycerol and acetate (Barton and Hamilton, 2007; Widdel, 1998; Brenner et al., 2005). These are also previously reported to be the dominant SRB groups in both sulfate and/or sulfite-reducing UASB reactors (Jiang et al., 2013; Qian et al., 2015b). In Stage I, with thiosulfate as the sole sulfur source, the total SRB population accounts for 42.6% at the genus level, of which *Desulfomicrobium* and *Desulfobulbus* make up 21.5 and 20.6%, respectively (see Fig. 2d). The enrichment of SRB in Stage I supports the high BTR and COD removal rate in UASB reactor without FSA and saline sulfite (Fig. 1a and b). When the reactor influent was supplemented with FSA at 6.0×10^{-4} mg S/L in Stage III, the total SRB abundance sharply decreased to 7.1% at the genus level. The levels of two major SRB genera, i.e. *Desulfobulbus* and *Desulfomicrobium* dropped to 3.4 and 0.8%, respectively. The small SRB population in Stage III corresponds to the low BTR activity (Fig. 1a and b). In Stage V, when FSA addition

was excluded, there was a recovery period according to performance that lasted for around 60 days (from Day 122 to Day 181). During that stage the SRB population rebounded to 33.1%, and this corresponded to the recovered BTR activity (see Fig. 1a and b). After this recovery, the *Desulfomicrobium* and *Desulfobulbus* levels rose to 21.1% and 11.6%, respectively. Based on the changes of microbial community and reactor performance at the different Stages, these strongly implicate a negative affect of FSA and saline sulfite on the SRB population.

Typically, in a sulfur reducing reactor operating for municipal sewage treatment, fermentation of organic compounds is an essential microbial process (Jiang et al., 2013). Although the single and simple organic compound (acetate, which is not fermentable) was utilized as electron donor and energy source in this study, certain levels of typical fermenting genera were still detected in the reactor communities (Fig. 2d). The most possible reason should be the sludge lysis to some extent as no sludge was purposely taken during the whole operation period. The organic products from cell lysis (the reactor had a long sludge retention time) and extracellular polymeric substances could contribute the fermentable substrates in the reactor (Wang et al., 2013, 2014). High abundance of *Trichococcus*, a well-known fermenting bacteria (Liu et al., 2002), was detected at 16.9% in Stage III (see Table S7), compared with 0.67 and 6.62% in Stages I and V. Thus, suggesting higher levels of fermentation occurred when FSA was added in Stage III, and possibly this was due to increased cell lysis caused by FSA, as has been reported for sludge treatment previously (Zan et al., 2016).

3.3 Effects of pH on the BTR

In Batch Test I the BTR activities were determined at different pH in the absence of saline sulfite and FSA (Fig. 3 and Fig. S4a). The BTR activity peaked at between 40 to 43 mg $\text{S}_2\text{O}_3^{2-}$ -S/g MLVSS/h at pH 7.0 and 8.0 (see Fig. 3a). This activity was 1.7 and 1.3 times that at pH 6.0 and 9.0 respectively. Also, this pH related trend is the same as that detected for biological co-sulfate/sulfite reduction where the reducing activity is also highest between pH 7.0 and 8.0 (Qian et al., 2015c). Consequently, this finding supports the notion that thiosulfate reduction is the rate-limiting step in biological sulfate/sulfite reduction.

(Position for Fig. 3)

3.4 The effects of saline sulfite and FSA concentrations on BTR

The effects of different Na_2SO_3 (that includes both saline sulfite and FSA) concentrations (50 to 200 mg S/L) on the BTR activity were examined in Batch Test II when the pH was controlled at 7.0 (Fig. 3b). It was seen that the highest biomass-specific thiosulfate reduction rate of 17.7 mg $\text{S}_2\text{O}_3^{2-}$ -S/g MLVSS/h was achieved with the lowest initial addition of Na_2SO_3 (50 mg S/L) and the activity continually lower when the higher initial Na_2SO_3 concentrations were added. Such that the biomass-specific $\text{S}_2\text{O}_3^{2-}$ reducing rate dropped by 39% when the Na_2SO_3 concentration increased from 50 mg S/L to 200 mg S/L (Fig. 3b). Therefore, the results of this test confirm that Na_2SO_3 consists of saline sulfite and FSA played a role in the inhibition of the BTR activity.

3.5 Correlation between FSA (H_2SO_3) and BTR activity

The BTR rates under different FSA levels were examined in Batch Test III. Both the pH and Na_2SO_3 concentrations were varied in each reactor in this test (Table S4). Based on the results from Batch Tests I, II and III, we examined for the correlations between BTR activity versus pH (Fig. 4a), BTR activity versus saline sulfite concentration (Fig. 4b) and BTR activity versus FSA concentration (Fig. 4c). As confirmed in Batch Test I, the pH really impacts the BTR activity, but the correlation between pH and BTR activity is not strong in the presence of Na_2SO_3 (Fig. 4a). At the same pH level, lower activity was observed at higher Na_2SO_3 concentrations. Generally, as the saline sulfite concentration increased, the BTR activity was reduced. However, this relationship also depends on pH (Fig. 4b). For example, with initial concentration of 200 mg S/L saline sulfite, the BTR activity varied from 4.4 to 33.6 mg $\text{S}_2\text{O}_3^{2-}$ -S/g MLVSS/h as the pH changed from 6.0 to 9.0. Therefore, the correlation between BTR and saline sulfite concentrations is also not strong. These observations imply that saline sulfite and pH jointly cause the inhibitory effect on thiosulfate reduction.

(Position for Fig. 4)

It was seen that the level of inhibition of the BTR had a strong correlation with the FSA concentration, indicating that FSA may be directly causing the inhibition (Fig. 4c). The inhibitory effect of FSA on the BTR was well described by an exponential function (Fig. 4c). The BTR activity decreased significantly with the increased FSA concentration even in the very low range of $0\sim 1.5\times 10^{-5}$ mg H_2SO_3 -S/L. The BTR activity decreased by 50% as FSA concentrations increased from 8.0×10^{-8} (Na_2SO_3 concentration of 100 mg S/L at pH 9.0) to

2.0×10⁻⁴ mg H₂SO₃-S/L (equivalent to a Na₂SO₃ concentration of 50 mg S/L at pH 7.0). When the FSA concentration increased from 8.0×10⁻⁸ (100 mg Na₂SO₃-S/L at pH 9.0) to 0.015 mg S/L (200 mg Na₂SO₃-S/L at pH 6.0), the BTR activity was inhibited by 90%. Consequently, these results suggest that FSA alone rather than saline sulfite or pH, is the true inhibitor of the BTR.

3.6 Toxicity and inhibition of FSA to microorganisms

Sulfite, either in the ionized form (saline sulfite: SO₃²⁻ + HSO₃⁻) or unionized form (FSA: H₂SO₃), is characterized as having potential toxicity to microbial metabolism. Its negative effects are suggested to be through damaging the biomacromolecules such as proteins, lipids and DNA (Armentia-Alvarez et al., 1993; Shi and Mao, 1994; Trotter and Grant, 2002; Pena-Egido et al., 2005), thus leading to the inhibition of microbial activity and growth. Other studies show that after exposure of microorganisms to sulfite, the cellular ATP levels are lowered and cell destruction is observed (Schimz and Holzer, 1979; Hinze and Holzer, 1986; Maier et al., 1986; Prakash et al., 1986). In addition, Park and Hwang (2008) provided the evidence that the addition of saline sulfite/FSA represses the expression of genes involved in transcription, protein biosynthesis and cell growth.

Other studies also show that the antimicrobial action of saline sulfite/FSA is found to be the greatest at low pH (Ough, 1993; Wedzichab, 1984), further adding support that H₂SO₃ (FSA) is the true antimicrobial agent rather than saline sulfite. The precise mechanisms of how FSA causes its antimicrobial effect is yet to be determined. The presence of FSA could change the structure of the cell membrane (Jiang et al., 2015), enter the cell and damage intracellular

components (Stratford and Morgan, 1987), and/or possibly directly cause cell lysis (Zan et al., 2016).

3.7 Implications of this study

Thiosulfate, as an intermediate of biological sulfate/sulfite reduction, is an effective electron donor for chemolithoautotrophic denitrification. Unlike the end product of biological sulfate/sulfite reduction, i.e. sulfide, thiosulfate is not reported to be toxic to microorganisms including the denitrifying bacteria (Cardoso et al., 2006). So use of thiosulfate as the electron donor in a wastewater treatment system could induce a high nitrogen removal rate as well as lead to a low sludge yield. Recently, we developed a “nitritation coupled with thiosulfate-driven denitritation (Nitritation-TDD)” process, that achieved a high biological ammonia-nitrogen removal rate of 0.43 kg NH₃-N/d/m³ (Qian et al., 2016). To facilitate the application of the Nitritation-TDD process, a key point is to ensure adequate thiosulfate is generated as thiosulfate is generally not directly available from the wastewater. This study on FSA inhibition of BTR provides some hints on how to obtain thiosulfate accumulation in a biological sulfate/sulfite reducing reactor’s effluent. By utilizing the inhibitory potential of FSA on BTR, an optimized sulfur cycle-driven biological process with three short-cut bioreactions is proposed here: 1) biological sulfate/sulfite reduction to thiosulfate ($\text{SO}_4^{2-}/\text{SO}_3^{2-} \rightarrow \text{S}_2\text{O}_3^{2-}$), 2) denitritation with thiosulfate as the electron donor ($\text{S}_2\text{O}_3^{2-} + \text{NO}_2^- \rightarrow \text{SO}_4^{2-} + \text{N}_2\uparrow$) and 3) nitritation ($\text{NH}_3 \rightarrow \text{NO}_2^-$). Consequently, this will result in higher nitrogen removal rates and lower sludge yields. The study to achieve this optimized process for co-treatment of wet flue gas desulfurization wastes with freshwater sewage is required and will be carried out in the near future.

396

397 **4. Conclusions**

398 The effects of FSA on biological thiosulfate reduction in a sulfur cycle-driven wastewater
399 treatment process were examined in this study. It was concluded that FSA, instead of saline
400 sulfite, is the true inhibitor of biological thiosulfate reduction. Based on the microbial
401 community analysis, the abundance of the SRB population in the thiosulfate-reducing UASB
402 reactor was sharply decreased from 46.2 to 7.1% at genus level when FSA was added to the
403 reactor's influent at 6.0×10^{-4} mg $\text{H}_2\text{SO}_3\text{-S/L}$. The biological thiosulfate reducing activity
404 decreased markedly with the addition of FSA, this was inhibited by 50% when initial FSA
405 concentrations were altered from 8.0×10^{-8} to 2.0×10^{-4} mg $\text{H}_2\text{SO}_3\text{-S/L}$ in the batch reactor. The
406 inhibition of FSA on biological thiosulfate reduction was found to recover after the elimination
407 of FSA.

408

409 **Acknowledgements**

410 This work was financially supported by Natural Science Foundation of China (No. 51608444)
411 and the Open Fund of State Key Laboratory of Geohazard Prevention and Geoenvironment
412 Protection (Grant No. SKLGP2017K026). The authors also gratefully acknowledge the support
413 from National Training Programs of Innovation and Entrepreneurship for undergraduate of
414 China (No. 201610699132 and No. 201610699369). Dr. Qilin Wang acknowledges the supports
415 of Australian Research Council Discovery Early Career Researcher Award (DE160100667),
416 Australian Research Council Discovery Project (DP170102812) and the Philanthropic Grant for
417 Early Career Engineering Researcher (GE12015).

418

419 **References**

420 APHA, 2005. Standard Methods for Water and Wastewater Examination. American Public
421 Health Association, Washington, D.C.

422 Armentia-Alvarez, A., Fernandez-Casero, A., Garcia-Moreno, C., Pena-Egido, M.J., 1993.
423 Residual levels of free and total sulphite in fresh and cooked burgers. Food Addit. Contam. 10,
424 157–165.

425 Barton, L.L., Hamilton, W.A., 2007. Sulphate-reducing Bacteria, Environmental and Engineered
426 Systems. Published in the United State of America by Cambridge University Press, New York.

427 Brenner, D.J., Krieg, N.R., Staley, J.T., 2005. Bergey's Manual[®] of Systematic Bacteriology. In:
428 The Proteobacteria Part C the Alpha-, Beta-, Delta-, and Epsilonproteobacteria, vol. 2.

429 Brunner, B., Bernasconi, S.M., 2005. A revised isotope fractionation model for dissimilatory
430 sulfate reduction in sulfate reducing bacteria. Geochim. Cosmochim. Ac. 69, 4759–4771.

431 Cardoso, R.B., Sierra-Alvarez, R., Rowlette, P., Flores, E.R., Gomez, J., Field, J.A., 2006.
432 Sulfide oxidation under chemolithoautotrophic denitrifying conditions. Biotechnol. Bioeng. 95,
433 1148–1157.

434 Castro, H.F., Williams, N.H., Ogram, A., 2000. Phylogeny of sulfate-reducing bacteria. FEMS
435 Microbiol. Ecol. 31, 1–9.

436 Chang, I.S., Kim, B.H., Shin, P.K., 1997. Use of sulfite and hydrogen peroxide to control
437 bacterial contamination in ethanol fermentation. Appl. Environ. Microbiol. 63 (1), 1–6.

438 Hinze, H., Holzer, H., 1986. Analysis of energy metabolism after incubation of *Saccharomyces*
439 *cerevisiae* with sulfite or nitrite. Arch. Microbiol. 145, 27–31.

440 Jiang, F., Zhang, L., Peng, G.L., Liang, S.Y., Qian, J., Wei, L., Chen, G.H., 2013. A novel
 441 approach to realize SANI process in freshwater sewage treatment – Use of wet flue gas
 442 desulfurization waste streams as sulfur source. *Water Res.* 47, 5773–5782.

443 Jiang, R., Wang, M., Xue, J., Xu, N., Hou, G., Zhang, W., 2015. Cytotoxicity of sulfurous acid
 444 on cell membrane and Bioactivity of *Nitrosomonas europaea*. *Chemosphere* 119, 896–901.

445 Lens, P.N.L., Visser, A., Janssen, A.J.H., Pol, L.W.H., Lettinga, G., 1998. Biotechnological
 446 treatment of sulfate-rich wastewaters. *Crit. Rev. Env. Sci. Technol.* 28, 41–88.

447 Liu, J.R., Tanner, R.S., Schumann, P., Weiss, N., McKenzie, C.A., Janssen, P.H., Seviour, E.M.,
 448 Lawson, P.A., Allen, T.D., Seviour, R.J., 2002. Emended description of the genus *Trichococcus*,
 449 description of *Trichococcus collinsii* sp. nov., and reclassification of *Lactosphaera pasteurii* as
 450 *Trichococcus pasteurii* comb. nov. and of *Ruminococcus palustris* as *Trichococcus palustris*
 451 comb. nov. in the low-GMC Gram-positive bacteria. *Int. J. Syst. Evol. Microbiol.* 52,
 452 1113–1126.

453 Maier, K., Hinze, H., Leuschel, L., 1986. Mechanism of sulfite action on the energy metabolism
 454 of *Saccharomyces cerevisiae*. *Biochim. Biophys. Acta.* 848, 120–130.

455 Manconi, I., Carucci, A., Lens, P., 2007. Combined removal of sulfur compounds and nitrate by
 456 autotrophic denitrification in bioaugmented activated sludge system. *Biotechnol. Bioengineering*
 457 98, 551–560.

458 Mora, M., Guisasola, A., Gamisans, X., Gabriel, D., 2014. Examining thiosulfate-driven
 459 autotrophic denitrification through Respirometry. *Chemosphere* 113, 1–8.

460 Muyzer, G., Stams, A.J.M., 2008. The ecology and biotechnology of sulphate-reducing bacteria.
 461 *Nat. Rev. Microbiol.* 6, 441–454.

462 Ough, C.S., 1993. Sulfur dioxide and sulfites, p. 137–190. In P.M. Davidson and A.L. Branen
 463 (eds.), *Antimicrobials in Foods*. Marcel Dekker Inc., New York, N.Y., USA.

464 O’Flaherty, V., Mahony, T., O’Kennedy, R., Colleran, E., 1998. Effect of pH on growth kinetics
 465 and sulphide toxicity thresholds of a range of methanogenic, syntrophic and sulphate-reducing
 466 bacteria. *Process Biochem.* 33, 555–569.

467 Park, S., Hwang, Y.S., 2008. Genome-Wide Transcription Responses to Sulfite in
 468 *Saccharomyces cerevisiae*. *J. Microbiol.* 46, 542–548.

469 Pena-Egido, M.J., Garcia-Alonso, B., Garcia-Moreno, C.J., 2005. S-Sulfonate contents in raw
 470 and cooked meat products. *Agric. Food. Chem.* 53, 4198–4201.

471 Prakash, D., Hinze, H., Holzer, H., 1986. Synergistic effect of mchloroperoxybenzoic acid,
 472 sulfite and nitrite on the energy metabolism of *Saccharomyces cerevisiae*. *FEMS Microbiol. Lett.*
 473 34, 305–308.

474 Qian, J., Jiang, F., Chui, H.K., van Loosdrecht, M.C.M., Chen, G.H., 2013. Industrial flue gas
 475 desulfurization waste may offer an opportunity to facilitate SANI[®] application for significant
 476 sludge minimization in freshwater wastewater treatment. *Water Sci. Technol.* 67, 2822–2826.

477 Qian, J., Lu, H., Jiang, F., Ekama, G.A., Chen, G.H., 2015a. Beneficial Co-Treatment of Simple
 478 Wet Flue Gas Desulphurization Wastes and Freshwater Sewage through Development of Mixed
 479 Denitrification–SANI process. *Chem. Eng. J.* 262, 109–118.

480 Qian, J., Liu, R., Wei, L., Lu, H., Chen, G.H., 2015b. System evaluation and microbial analysis
 481 of a sulfur cycle-based wastewater treatment process for Co-treatment of simple wet flue gas
 482 desulfurization wastes with freshwater sewage. *Water Res.* 80, 189–199.

483 Qian, J., Lu, H., Cui, Y., Wei, L., Liu, R., Chen, G.H., 2015c. Investigation on
484 Thiosulfate-involved Organics and Nitrogen Removal by a Sulfur Cycle-based Biological
485 Wastewater Treatment Process. *Water Res.* 69, 295–306.

486 Qian, J., Zhou, J., Zhang, Z., Liu, R., Wang, Q., 2016. Biological nitrogen removal through
487 nitrification coupled with thiosulfate-driven denitrification. *Sci. Rep.* 6:27502.

488 Quince, C., Lanzen, A., Davenport, R., Turnbaugh, P.J., 2011. Removing noise from
489 pyrosequenced amplicons. *BMC Bioinformatics* 12, 38–56.

490 Ren, N., Wang, A., Zhao, Y., 2009. Ecology of sulfate-reducing bacteria in anaerobic treatment
491 processes, Science, Beijing.

492 Sahinkaya, E., Dursun, N., 2012. Sulfur-oxidizing autotrophic and mixotrophic denitrification
493 processes for drinking water treatment: Elimination of excess sulfate production and alkalinity
494 requirement. *Chemosphere* 89, 144–149.

495 Schimz, K.L., Holzer, H., 1979. Rapid Decrease of ATP Content in Intact Cells of
496 *Saccharomyces cerevisiae* After Incubation with Low Concentrations of Sulfite. *Arch. Microbiol.*
497 121, 225–229.

498 Shi, X., Mao, Y., 1994. 8-Hydroxy-20-deoxyguanosine formation and DNA damage induced by
499 sulfur trioxide anion radicals. *Biochem. Biophys. Res. Commun.* 205, 141–148.

500 Stratford, M., Morgan, P., Rose, A.H., 1987. Sulphur dioxide resistance in *Saccharomyces*
501 *cerevisiae*. *J. Gen. Microbiol.* 133, 2173–2179.

502 Trotter, E.W., Grant, C.M., 2002. Thioredoxins are required for protection against a reductive
503 stress in the yeast *Saccharomyces cerevisiae*. *Mol. Microbiol.* 46, 869–878.

504 Wang, Q., Ye, L., Jiang, G., Jensen, P., Batstone, D., Yuan, Z., 2013. Free nitrous acid (FNA)-

505 based pre-treatment enhances methane production from waste activated sludge. *Environ. Sci.*
 506 *Technol.* 47, 11897-11904.

507 Wang, Q., Jiang, G., Ye, L., Yuan, Z., 2014. Enhancing methane production from waste
 508 activated sludge using combined free nitrous acid and heat pre-treatment. *Water Res.* 63, 71-
 509 80.

510 Wedzichab, L., 1984. *Chemistry of Sulphur Dioxide in Foods*. London: Elsevier Applied
 511 Science Publishers.

512 Weijma, J., Hulshoff, P.L.W., Stams, A.J.M., Lettinga, G., 2000. Performance of a thermophilic
 513 sulfate and sulfite reducing high rate anaerobic reactor fed with methanol. *Biodegradation* 11,
 514 429–439.

515 Widdel, F., 1988. Microbiology and ecology of sulfate-and sulfur-reducing bacteria. In: *Biology*
 516 *of Anaerobic Microorganisms* (A. Zehnder, ed.).

517 Zan, F., Hao, T., Chi, K., Ekama, G.A., Chen, G.H., 2016. Using sulfite pretreatment to improve
 518 the biodegradability of waste activated sludge. *RSC Adv.* 6, 71875–71881.

519 **List of Figures and tables**

520 **Fig. 1** Thiosulfate reduction/sulfide generation **(a)** and performance of organic removal **(b)** in
521 the biological thiosulfate-reducing UASB reactor.

522 **Fig. 2 (a)** Rarefaction analysis of the sludge samples at Stages I, III and V, respectively. **(b)** and
523 class **(c)** levels using RDP classifier with a confidence threshold of 97%; **(d)** Relative abundance
524 and phylogenetic relationships of different genera retrieved from the sludge (the phylogenetic
525 relationships were calculated by visualizing as a heatmap and using MeV software. The color
526 indicates the percentage of a genus in total sequences).

527 **Fig. 3 (a)** Biomass-specific thiosulfate reduction rates versus pH in Batch Test I; **(b)**
528 Biomass-specific thiosulfate reduction rates versus Na_2SO_3 concentrations in Batch Test II.

529 **Fig. 4** Biological thiosulfate reducing activities under different pH conditions **(a)** and different
530 saline sulfite concentrations **(b)** and **(c)** Correlation between thiosulfate reduction rates versus
531 FSA concentrations in the 10 batch reactors including 4 batch reactors in Batch Test II and 6
532 batch reactors in Batch Test III.

Fig. 1 Thiosulfate reduction/sulfide generation (a) and performance of organic removal (b) in the biological thiosulfate-reducing UASB reactor

Fig. 3 (a) Biomass-specific thiosulfate reduction rates versus pH in Batch Test I; **(b)** Biomass-specific thiosulfate reduction rates versus Na_2SO_3 concentrations in Batch Test II.

Fig. 4 Biological thiosulfate reducing activities under different pH conditions **(a)** and different saline sulfite concentrations **(b)** and **(c)** Correlation between thiosulfate reduction rates versus FSA concentrations in the 10 batch reactors including 4 batch reactors in Batch Test II and 6 batch reactors in Batch Test III.

Highlights

- Free sulfurous acid was the true inhibitor of biological $\text{S}_2\text{O}_3^{2-}$ reduction
- $\text{S}_2\text{O}_3^{2-}$ reducing activity was depressed at an FSA concentration of 1.5×10^{-5} mg S/L.
- $\text{SO}_4^{2-}/\text{SO}_3^{2-}$ -reducing bacteria population decreased in the presence of FSA
- FSA inhibition on biological $\text{S}_2\text{O}_3^{2-}$ reduction is reversible